

[First Hit](#)      [Previous Doc](#)      [Next Doc](#)      [Go to Doc#](#)  
**End of Result Set**

☐ [Generate Collection](#) [Print](#)

L25: Entry 14 of 14

File: JPAB

Feb 3, 1998

PUB-NO: JP410031515A

DOCUMENT-IDENTIFIER: JP 10031515 A

TITLE: CONTROL METHOD FOR AUTOMATED GUIDE VEHICLE AND AUTOMATED GUIDED DEVICE

PUBN-DATE: February 3, 1998

INVENTOR-INFORMATION:

NAME

COUNTRY

IWASAKI, MASAOKI

SUGIYAMA, MASATOSHI

NARUO, TAKANOBU

DEGAWA, SADAOKI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

ISHIKAWAJIMA HARIMA HEAVY IND CO LTD

APPL-NO: JP08185206

APPL-DATE: July 15, 1996

INT-CL (IPC): G05D 1/02; H04Q 7/34

ABSTRACT:

PROBLEM TO BE SOLVED: To provide an inexpensive automated guide device which can easily change a transportation path by permitting an automated guided vehicle to transmit an entering request to a monitor area to a ground control board and permitting the control board to judge the propriety of entering based on position information of the other automated guided vehicle to return information.

SOLUTION: The ground control board 1 judges whether an automated guided vehicle AGV 2 is to be entered into the monitor area 4 or not when it receives an entering request signal from the (AGV) 2A and 2B through a communication line, AGV2A, for example. An entering permission signal or a standby indication signal is transmitted in accordance with the judged result. The monitor area 4 is previously provided at a place where AGV2A and 2B possible simultaneously pass through like a crossing X on the transportation path 3, for example. When AGV2A receives the entering permission signal, it enters into the monitor area 4 and transmits a passage notice signal to the ground control board when it passes through the monitor area 4.

COPYRIGHT: (C)1998, JPO

[Previous Doc](#)      [Next Doc](#)      [Go to Doc#](#)